

主要外部及连接

单位:毫米

通径	主要外部及连接										WT (kg)	
	L	D	D1	D2	b	Y	f2	Z-Φd	H	W		
	Q41F-25	Q41F-25P	Q641F-25	Q641F-25P	Q9B41F-25	Q9B41F-25P						
15	130	95	65	45	16	-	-	4-Φ14	103	100	3	
20	140	105	75	55	16	-	-	4-Φ14	112	160	4	
25	150	115	85	65	16	-	-	4-Φ14	123	160	6	
32	165	135	100	78	18	-	-	4-Φ18	150	250	10	
40	180	145	110	85	18	-	-	4-Φ18	156	250	14	
50	200	160	125	100	20	-	-	4-Φ18	172	350	20	
65	220	180	145	120	22	-	-	8-Φ18	197	350	25	
80	250	195	160	135	22	-	-	8-Φ18	222	450	30	
100	280	230	190	160	24	-	-	8-Φ23	253	450	40	
125	320	270	220	188	28	-	-	8-Φ25	275	600	65	
150	360	300	250	218	30	-	-	8-Φ25	286	800	85	
200	400	360	310	278	34	-	-	12-Φ25	340	1200	100	
250	533	425	370	332	36	-	-	12-Φ30	470	1400	165	
	Q41F-40	Q41F-40P	Q341F-40	Q341F-40P	Q641F-40	Q641F-40P	Q9B41F-40	Q9B41F-40P				
15	130	95	65	45	16	40	4	4-Φ14	103	100	3	
20	140	105	75	55	16	51	4	4-Φ14	112	160	4	
25	150	115	85	65	16	58	4	4-Φ14	123	160	6	
32	180	135	100	78	18	66	4	4-Φ18	150	250	10	
40	200	145	110	85	18	76	4	4-Φ18	156	250	14	
50	220	160	125	100	20	88	4	4-Φ18	172	350	20	
65	250	180	145	120	22	110	4	8-Φ18	197	350	25	
80	280	195	160	135	22	121	4	8-Φ18	222	450	30	
100	320	230	190	160	24	150	4.5	8-Φ23	253	450	40	
125	400	270	220	188	28	176	4.5	8-Φ25	275	600	65	
150	400	300	250	218	30	204	4.5	8-Φ25	286	800	85	
200	550	375	320	282	38	260	4.5	12-Φ30	340	1200	100	
250	568	445	385	345	42	313	4.5	12-Φ34	470	1400	165	
	Q41F-63	Q41F-63P	Q341F-63	Q341F-63P	Q641F-63	Q641F-63P	Q9B41F-63	Q9B41F-63P				
15	140	105	75	55	18	40	4	4-Φ14	105	130	3.1	
20	155	125	90	68	20	51	4	4-Φ18	125	130	4.9	
25	180	135	100	78	22	58	4	4-Φ18	135	160	7.2	
32	200	150	110	82	24	66	4	4-Φ23	150	160	8.7	
40	220	165	125	95	24	76	4	4-Φ23	165	230	12.1	
50	250	175	135	105	26	88	4	4-Φ23	175	230	16.7	
65	280	200	160	130	28	110	4	8-Φ23	200	400	28.2	
80	320	210	170	140	30	121	4	8-Φ23	210	400	36	
100	350	250	200	168	32	150	4.5	8-Φ25	250	700	66	
125	455	295	240	202	36	176	4.5	8-Φ30	295	1100	98	
150	495	340	280	240	38	204	4.5	8-Φ34	340	1500	142	